

Optical TSS sensor with low maintenance

RELIABLE OPERATION, NO TEAR AND WEAR PARTS













Measure suspended solids to calculate the sludge age

Advatanges:

- Low maintenance by integrated ultrasonic cleaning
- No exchange of O-rings or movable parts
- Service contract not mandatory
- High operational safety (sensor check function)

The ultrasonic cleaning system ensures the low-maintenance and continuously reliable measuring operation.



Without ultrasound cleaning system



With ultrasound cleaning system

Technical Data

ViSolid® 700 IQ (SW)			
Scattered light measurement			
SiO ₂ TSS	0.01 300 g/l 0.003 1000 g/l	0.001 30 % 0.0003 100 %	
Integrated ultrasonic cleaning			
0 +60 °C			
10 bar			
	Scattered SiO ₂ TSS Integrated 0 +60 °	Scattered light measurement SiO ₂ 0.01 300 g/l TSS 0.003 1000 g/l Integrated ultrasonic cleaning 0 +60 °C	Scattered light measurement SiO ₂ 0.01 300 g/l 0.001 30 % TSS 0.003 1000 g/l 0.0003 100 % Integrated ultrasonic cleaning 0 +60 °C





Ordering Information

Model	Description	Order No.
ViSolid® 700 IQ	Digital suspended solids sensor with integrated ultrasonic cleaning (please order cable separately)	600012
ViSolid® 700 IQ SW	Like ViSolid® 700 IQ, but as a sea water model	600013



Xylem Analytics Germany Sales GmbH & Co. KG, WTW \cdot Am Achalaich 11 \cdot 82362 Weilheim \cdot Germany Phone +49 881 1830 \cdot Fax +49 881 183-420 \cdot Info.WTW@Xylem.com \cdot www.xylemanalytics.com